LINESCAPES CANTILEVERED

Family of floor, ceiling and wall lamps, efficient with an highly versatile linear luminous output. Structure in aluminium extruded and opal white polycarbonate diffuser. Horizontal cantilever wall version supplied with kit for connection with remote driver. White or balck finishing with elements in grey painted on the floor and wall versions.



LED 2700K

LAMPING

Source linear LED
Total power 12W

Emission diffused orientable

Tension 24V DC
Color temperature 2700K
Luminous flux 475Im
Typ CRI 85
Energy class A+

Materials Aluminium + PC + ABS

Notes driver not included, recessing box included, wall board for

installation included, side emission, orientable 340°,

recessed hole 13x11cm depth 9cm

Net lamp weight 1,5 kg

Codes Structure
LIN LW2 34 white

PACKAGE

Package 01 Dimension: 20x15x145 cm / Gross weight: 3 kg

Certificazioni

C € EHE



LED 3000K

LAMPING

Source linear LED
Total power 12W

Emission diffused orientable

Tension 24V DC
Color temperature 3000K
Luminous flux 475Im
Typ CRI 85
Energy class A+

Materials Aluminium + PC + ABS

Notes driver not included, recessing box included, wall board for

installation included, side emission, orientable 340°,

recessed hole 13x11cm depth 9cm

Net lamp weight 1,5 kg

Codes Structure
LIN LWW 34 white

PACKAGE

Package 01 Dimension: 20x15x145 cm / Gross weight: 3 kg

Certificazioni

C € EHE

