SPIGOLO WALL CEILING

Studiocharlie

Floor, wall/ceiling, pendant and table lamps based on an extruded and tubular aluminium structure, connected with moulded polymer joints, with white or black painted finish. Thanks to the joints, enabling the profiles to house LED sources, one can rotate 360° in order to produce a directional direct or indirect lighting, screened by an opaline diffuser in polycarbonate. The floor version is designed as such to provide a virtual divider to ambiences, while the ceiling and wall versions allow the enlightenment of the ambience in a versatile and a comfortable way.



LED 2700K

LAMPING

Source linear LED
Total power 14W

Emission orientable, diffused

Tension 110/240V
Color temperature 2700K
Luminous flux 560Im
Typ CRI 85
Energy class A+

Materials aluminium + PC + ABS

Notes orientable diffuser 360°

Net lamp weight 1,5 kg

Codes Structure


SPI LW2 31 white SPI LN2 31 black

PACKAGE

Package 01 Dimension: 30x45x20 cm / Gross weight: 2,1 kg

Certificazioni

C € ERI



LED 3000K

LAMPING

Source linear LED
Total power 14W

Emission orientable, diffused

Tension 110/240V
Color temperature 3000K
Luminous flux 560Im
Typ CRI 85
Energy class A+

Materials aluminium + PC + ABS
Notes orientable diffuser 360°

Net lamp weight 1,5 kg

Codes Structure

SPI LWW 31 white SPI LNN 31 black

PACKAGE

Package 01 Dimension: 30x45x20 cm / Gross weight: 2,1 kg

Certificazioni

C € ERI

